Commonwealth of Kentucky Division for Air Quality

PERMIT APPLICATION SUMMARY FORM

(For all sources except PSD and true minor sources)

Completed by: Jill Bertelson, Permit Reviewer

GENERAL INFORMATION:			
Name:	Progress Rail	Services Corp	oration
Address:	8587 Railroad	8587 Railroad Drive, Covington, KY 41015-0399	
Date application received:		December 13, 1996	
SIC/Source description:	4789		
AFS(10-digit) Plant ID:	21-117-00154	1	
EIS #:	079-2020-0154		
Application log number:	E860		
Permit number:	V-98-038		
APPLICATION TYPE/PERMIT ACTIVITY	<u>ΓΥ</u> :		
[X] Initial issuance		[] General permit	
[] Permit modification		[] Conditional major	
Administrative		[X] Title V	•
Minor		[X] Syntheti	c minor
Significant		[X] Operating	
Permit renewal		[] Construction/operating	
COMPLIANCE SUMMARY: [] Source is out of compliant [X] Compliance certification		[] Complian	ce schedule included
APPLICABLE REQUIREMENTS LIST:			
AFFEICABLE REQUIREMENTS EIST. [] NSR [] NS	SDS.	[X] SIP	
	ESHAPS	[X] Other:	Promulgated CTG RACT
[][0]	LSIIAI S	[A] Other.	Tromulgated CTO KACT
Miscellaneous:			
[] Acid rain source			
[] Source subject to 112(r)			
[X] Source applied for feder	ally enforceable	e emissions cap)
Source provided terms for	•	-	-
[] Source subject to a MAC	CT standard	C	
[] Source requested case-by		r (j) determinat	ion
[] Application proposes nev		•	
[X] Certified by responsible		23	
[X] Diagrams or drawings in			
[] Confidential business inf) submitted in a	application
[] Pollution Prevention Me	, ,	,	T F
[X] Area is non-attainment (Ozone (mode	erate)

EMISSIONS SUMMARY:

Pollutant	Actual (tpy)	Potential (tpy)
PM	71.6	71.6
SO_2	0	0
NOx	6	6
CO	0.8	0.8
VOC	180	630.3
LEAD	0.04	0.04
HAP ≥ 10 tpy (by CAS)		
78-93-3 MEK	127.1	127.1
100-41-4 Ethyl benzene	16.1	16.1
108-10-1 MIBK	35.8	35.8
108-88-3 Toluene	129.6	129.6
111-76-2 Butyl Cellosolve	61.0	61.0
569-01-3 Xylene	126.7	126.7
91-20-3 Napthalene	12.5	12.5

SOURCE PROCESS DESCRIPTION:

The existing shop houses a railcar repainting process consisting of a grit blast booth, spray painting booth with direct heating for the winter months, drying room with indirect heaters, and a stencil room with painting and indirect heaters. Railcars are blasted with steel grit or coal slag to remove the existing paint in the blast booth. Airless spray guns with low-VOC coatings are used in the spray paint booth. A bucket parts washer is used to periodically clean the spray guns. All of the heaters use propane as fuel.

The new shop consists of one room housing railcar repair operations consisting of welding, air arc gouging, oxygen cutting, grinding, caulking, fiberglass work, and painting. There are also parts washers, propane-fired space heaters, and fuel tanks associated with the New Shop.

All waste is picked up by a private waste services company and all waste solvent is picked up by the parts washers and solvent manufacturer.

EMISSION AND OPERATING CAPS DESCRIPTION:

There is a synthetic minor limit of 90 TPY on VOC emissions from the first construction project, which consists of the Spray Paint Booth painting and direct heater, Drying Room indirect heat exchangers, Stencil Room painting and indirect heat exchangers, and regulated parts washer. The permit limit covering both painting operations is adjusted for the maximum VOC emissions from the heaters and parts washer. This precludes applicability of 401 KAR 51:052.

There is a synthetic minor limit of 90 TPY on VOC emissions from the second construction project, which consists of the New Shop painting and insignificant activities. The permit limit covering the painting operation is adjusted for the maximum VOC emissions from the insignificant activities. This precludes applicability of 401 KAR 51:052.

OPERATIONAL FLEXIBILITY:

Spray Paint Booth, Stencil Room painting, New Shop painting: can use any paint system with <3.5 lb VOC/gal. The VOC content of a paint system is as-applied including thinners and solvents added. The permittee can use any clean-up solvent as long as the synthetic minor limits are not violated.